

## ASFA S (12 mm) Hose Clamp AISI 430 Stainless Steel - W2



W2

This clamp represents the latest stage in the evolution of the ASFA 12mm range. One of the main developments in this version is the lateral displacement of the band thread, which reduces the tendency of the band end to exit the housing off-centre when tightened.

Thanks to the combination of the housing, locking system and the location of the screw within the housing, this clamp offers superior performance at the same torque ratings.

Specially recommended for industrial applications.

DIN 3017. The ASFA SW2 hose clip complies fully with the DIN 3017 norm and also with the directive EU 2002/95/EC.

*\* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.*

Application Ø										
mm	Part nº	L max.	S +0,10	h max.	a +0,3 a -0,1	b max.	Maximum values		Box Quantity (MOQ)	Outer Packing
							Torque (Nm)	Pressure (Bars)		
16-27	0301701-7	29,6	0,85	11	12,2	16,7	4,5	40	50	400
20-32	0301702-5	29,6	0,85	11	12,2	16,7	5,5	40	50	400
25-40	0301703-3	29,6	0,85	11	12,2	16,7	5,5	40	50	400
30-45	0301700-9	29,6	0,85	11	12,2	16,7	5,5	35	50	400
32-50	0301704-1	29,6	0,85	11	12,2	16,7	6,5	35	50	200
40-60	0301705-0	29,6	0,85	11	12,2	16,7	6,5	30	50	400
50-70	0301706-8	29,6	0,85	11	12,2	16,7	7	25	50	400
60-80	0301707-6	29,6	0,85	11	12,2	16,7	7	20	50	50
70-90	0301708-4	29,6	0,85	11	12,2	16,7	7	17	50	50
80-100	0301709-2	29,6	0,85	11	12,2	16,7	7	14	25	200
90-110	0301710-5	29,6	0,85	11	12,2	16,7	7	12	25	200
100-120	0301711-3	29,6	0,85	11	12,2	16,7	7	10	25	200
110-130	0301712-1	29,6	0,85	11	12,2	16,7	7	8	25	25
120-140	0301713-0	29,6	0,85	11	12,2	16,7	7	7	25	25
130-150	0301714-8	31,6	0,85	11	12,2	16,7	7	6	25	25
140-160	0301715-6	31,6	0,85	11	12,2	16,7	7	5	25	25
150-170	0301716-4	31,6	0,85	11	12,2	16,7	7	4	25	25
160-180	0301717-2	31,6	0,85	11	12,2	16,7	7	3	25	25
170-190	0301718-0	31,6	0,85	11	12,2	16,7	7	2	10	10
180-200	0301719-9	31,6	0,85	11	12,2	16,7	7	2	10	10
190-210	0301720-1	31,6	0,85	11	12,2	16,7	7	1,8	10	10
200-220	0301721-0	31,6	0,85	11	12,2	16,7	7	1,8	10	10
210-230	0301722-8	31,6	0,85	11	12,2	16,7	7	1,6	10	10
220-240	0301723-6	31,6	0,85	11	12,2	16,7	7	1,6	10	10

*\* It is recommended to apply 75% of the maximum values contained in the table.*

TECHNICAL INFORMATION	
<b>MATERIAL</b>	BAND AND HOUSING: INOXIDABLE (AISI-430) SCREW: STEEL Qst 36-3 (DIN 1.0214)
<b>FINISH</b>	BAND AND HOUSING: STAINLESS STEEL SCREW: GREY-WHITE Cr3 ZINC-PLATED
<b>CORROSION RESISTANCE</b>	72 HOURS SALT SPRAY (ASTM B-117)
<b>MAXIMUM TIGHTENING SPEED (RPM)</b>	540 ±5

