



W3

## ASFA S (12 mm) Hose Clamp AISI 430 Stainless Steel - W3

This clamp represents the latest stage in the evolution of the ASFA 12mm range. One of the main developments in this version is the lateral displacement of the band thread, which reduces the tendency of the band end to exit the housing off-centre when tightened.

Thanks to the combination of the housing, locking system and the location of the screw within the housing, this clamp offers superior performance at the same torque ratings.

Specially recommended for automotive applications.

DIN 3017. The ASFA SW3 hose clip complies fully with the DIN 3017 norm and also with the directive EU 2002/95/EC.

*\* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.*

Application Ø										
mm	Part nº	L max.	S +0,10	h max.	a +0,3 a -0,1	b max.	Maximum values		Box Quantity (MOQ)	Outer Packing
							Torque (Nm)	Pressure (Bars)		
16-27	0301620-9	29,6	0,85	11	12,2	16,7	4,5	40	50	400
20-32	0301621-7	29,6	0,85	11	12,2	16,7	5,5	40	50	400
25-40	0301622-5	29,6	0,85	11	12,2	16,7	5,5	40	50	400
30-45	0301623-3	29,6	0,85	11	12,2	16,7	5,5	35	50	400
32-50	0301624-1	29,6	0,85	11	12,2	16,7	6,5	35	50	200
40-60	0301625-0	29,6	0,85	11	12,2	16,7	6,5	30	50	400
50-70	0301626-8	29,6	0,85	11	12,2	16,7	7	25	50	400
60-80	0301627-6	29,6	0,85	11	12,2	16,7	7	20	50	50
70-90	0301628-4	29,6	0,85	11	12,2	16,7	7	17	50	50
80-100	0301629-2	29,6	0,85	11	12,2	16,7	7	14	25	200
90-110	0301630-5	29,6	0,85	11	12,2	16,7	7	12	25	200
100-120	0301631-3	29,6	0,85	11	12,2	16,7	7	10	25	200
110-130	0301632-1	29,6	0,85	11	12,2	16,7	7	8	25	25
120-140	0301633-0	29,6	0,85	11	12,2	16,7	7	7	25	25
130-150	0301634-8	31,6	0,85	11	12,2	16,7	7	6	25	25
140-160	0301635-6	31,6	0,85	11	12,2	16,7	7	5	25	25
150-170	0301636-4	31,6	0,85	11	12,2	16,7	7	4	25	25
160-180	0301637-2	31,6	0,85	11	12,2	16,7	7	3	25	25
170-190	0301638-0	31,6	0,85	11	12,2	16,7	7	2	10	10
180-200	0301639-9	31,6	0,85	11	12,2	16,7	7	2	10	10
190-210	0301642-8	31,6	0,85	11	12,2	16,7	7	1,8	10	10
200-220	0301643-6	31,6	0,85	11	12,2	16,7	7	1,8	10	10
210-230	0301644-4	31,6	0,85	11	12,2	16,7	7	1,6	10	10
220-240	0301645-2	31,6	0,85	11	12,2	16,7	7	1,6	10	10

*\* It is recommended to apply 75% of the maximum values contained in the table.*

TECHNICAL INFORMATION	
<b>MATERIAL</b>	BAND AND HOUSING: STAINLESS STEEL X6Cr17 (AISI-430) SCREW: STAINLESS STEEL (AISI-304 CU)
<b>FINISH</b>	STAINLESS STEEL
<b>CORROSION RESISTANCE</b>	200 HOURS SALT SPRAY (ASTM B-117)
<b>MAXIMUM TIGHTENING SPEED (RPM)</b>	540 ±5

