

## OEM Ear Clip



W1

This clamp was designed for use in low and medium-pressure applications on assembly lines, due to its fast and easy locking system.

The design of the locking mechanism means that this clamp can be used in areas which are difficult to access. In this case manual pliers can be used to mount the clip.

Another very important characteristic of this clamp is that once it has been mounted it is tamper-proof.

*\* This clamp is also available in AISI 304 and AISI 316 material upon request.*

Application Ø							
D ±0,3 mm	Closed Ø D min.	Part nº	H max. mm	S ±0,3 mm	a ±0,15	Box Quantity (MOQ)	Outer Packing
10,0	8,3	0303075-2	14,0	0,6	7	1.000	4.000
13,3	10,8	0303076-0	17,0	0,6	7	1.000	4.000
15,7	13,2	0303077-9	20,1	0,6	7	1.000	4.000
17,5	14,3	0303078-7	22,5	0,8	7	1.000	4.000
17,8	14,6	0303079-5	22,5	0,8	7	1.000	4.000
18,5	15,3	0303080-8	23,5	0,8	7	1.000	4.000
20,5	17,3	0303081-6	26,0	0,8	7	500	2.000
29,5	26,3	0303082-4	35,5	0,8	7	500	2.000
31,6	28,4	0303083-2	37,5	0,8	7	500	2.000
39,6	36,4	0303084-0	45,5	0,8	7	500	1.000
40,5	37,3	0303085-9	46,5	0,8	7	500	1.000
45,5	42,3	0303086-7	51,5	0,8	7	200	800
47,0	43,8	0303087-5	53,0	0,8	7	200	800
51,5	48,3	0303088-3	57,5	0,8	7	100	400
52,5	49,3	0303089-1	58,5	0,8	7	100	400
65,5	62,3	0303090-4	71,5	0,8	7	100	400

	TECHNICAL INFORMATION	
	<b>MATERIAL</b>	STEEL DX51D+ AZ 150 (UNI EN 10215)
	<b>FINISH</b>	GREY-WHITE (ALUZINK)
	<b>CORROSION RESISTANCE</b>	144 HOURS SALT SPRAY (ASTM B-117)

